

VistaPlex Camera Pricing

fall 2011

			Vandalproof Dome Camera	
			3-Axis bracket built-in	
			OSD Menu controlled by cable button	
VPVWD28E	\$119	Color 1/3" SONY ICX673AK CCD, Effio-E 700TV Lines Low Illumination, ATR, OSD, DNR	2.8-12mm Manual Zoom Lens Dimension: \varnothing 117x 92(H) mm Weight:800g	
			Weatherproof IR camera	
			IR LED: \varnothing 8X36PCS IR LED working distance: 50M	
			Water resistance: IP66	
			Build in auto temperature control	
VPWIRLP5E	\$199	Color 1/3" SONY ICX673AK CCD, Effio-E 700TV Lines Low Illumination, ATR, OSD, DNR	OSD Menu controlled by cable button (standard) OSD Menu controlled by RS485 (optional) Lens: 5-15mm Manual Zoom Lens Dimension:230(W)x180(H)x115(D)mmWeight:2.1Kg	
			Weatherproof &Vandalproof Dome Camera	
			Outdoor design, Water resistance: IP66	
			3-Axis bracket built-in	
			OSD Menu controlled by cable button (standard)	
VPVWVD28E	\$179	Color 1/3" SONY ICX673AK CCD, Effio-E 700TV Lines Low Illumination, ATR, OSD, DNR	OSD Menu controlled by RS485 (optional) 2.8-12mm Manual Zoom Lens optional Size: \varnothing 138x212mm Weight: 2.8Kg	
			★Vandalproof Mini PTZ Speed Dome camera	
			★Pan range: 0°~360° Continue (Not 355°)	
			★Tilt range: 0°~90° Flip	
			★Pan Speed: Max 50°/sec Preset: 16	
VPVPTZ10X	\$369	SAMSUNG 10X SDM-100,1/4" Super HAD Color CCD ,ICR, 10X(f=3.8~38mm),Color 500TVL,Black 570TVL	★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★10X(f=3.8~38mm) ★Size: \varnothing 138x212mm Weight: 2.8Kg	
			★360 Degree Mini PTZ Speed Dome camera	
			★Pan range: 0°~360° Continue (Not 355°)	
			★Tilt range: 0°~90° Flip	
			★Pan Speed: Max 50°/sec ★Preset: 16	
VPPTZD515E	\$269	Color 1/3" SONY ICX673AK CCD, Effio-E 700TV Lines Low Illumination, ATR, OSD, DNR	★RS485, Pelco D/P supported ★Two brackets included (for Ceiling & Side mount) ★OSD Menu controlled by RS485 ★5-15mm dynamic varifocal lens ★Size: \varnothing 138x266mm Weight: 2.8Kg	